



YOUR MANUAL BATTERY SWITCH SOLUTIONS



MAXICUT

YOUR MANUAL BATTERY SWITCH SOLUTIONS

MAXICUT[®]

CONTENTS

BATTERY SWITCH Manual control p. 2

ACCESSORIES AND SPARE PARTS..... p. 5



BATTERY MASTER SWITCH - MANUAL CONTROL

SINGLE POLE

M10 SERIES



GENERAL CHARACTERISTICS

IP54

+80 C
-30 C

PA66
glass
filled

100 g

M8



- Continuous rating 100 A
- Overload 500 A - 10 s.
- Ground & positive Cut-off

PRODUCT SELECTION

P/N	HANDLE		TERMINALS	
	TYPE	COLOR AND MATERIAL	LENGTH	MATERIAL
624542	Removable in OFF position	Red thermoplastic	6 mm	Copper

On request: specific technical demand can be studied

ACCESSORIES

HANDLE
901 SERIES
202802



BATTERY MASTER SWITCH - MANUAL CONTROL

SINGLE POLE

M20 SERIES



GENERAL CHARACTERISTICS

IP65

+80 C
-30 C

PA66
glass
filled

200 g

M10



- Continuous rating 160 A
- Overload 1500 A - 5 s.
- Ground & positive Cut-off

PRODUCT SELECTION

P/N	HANDLE		TERMINALS	
	TYPE	COLOR AND MATERIAL	LENGTH	MATERIAL
600002	Fixed / 2 positions	Red thermoplastic	3,5 mm	Copper

On request: specific technical demand can be studied

ACCESSORIES

HEIGHTENED TERMINAL		TERMINAL INSULATION CAP	
900 SERIES	200588	900 SERIES Red	201010
		900 SERIES Black	202499



BATTERY MASTER SWITCH - MANUAL CONTROL

SINGLE POLE

M60 SERIES



GENERAL CHARACTERISTICS

- IP65
- +80 C
-30 C
- PA66
glass filled
+ steel
- 400 g
- M10



- Continuous rating 315 A
- Overload 2500 A - 5 s.
- Ground & positive Cut-off
- Handle: Fixed / 2 positions

OPTIONS

Auxiliary circuit

PRODUCT SELECTION

P/N	WEIGHT	HANDLE		TERMINALS		AUXILIARY CIRCUIT		
		TYPE	COLOR AND MATERIAL	LENGTH	MATERIAL	TYPE	CONTINUOUS RATING	CONNECTION
612022	350 g	Removable only for the mounting	Red thermoplastic	3,5 mm	Copper	D+	10 A	M5
612702	400 g	Removable only for the mounting / Unclipped in OFF position	Red thermoplastic	3,5 mm	Copper	-	-	-
613002	400 g	Removable only for the mounting	Red thermoplastic	3,5 mm	Copper	-	-	-
613402	400 g	Heightened / Removable only for the mounting	Red thermoplastic	3,5 mm	Copper	-	-	-

On request: specific technical demand can be studied

ACCESSORIES

CHAIN		TERMINAL INSULATION CAP	
900 SERIES	200894	900 SERIES Red	201010
		900 SERIES Black	202499
HEIGHTENED TERMINAL			
900 SERIES			200588

901 SERIES



HANDLE		202802
COLOR		MATERIAL
Red		Thermoplastic
To use with:		
M10: 624542		

900 SERIES



CHAIN		200894
COLOR		MATERIAL
Metallic		Steel
To use with:		
M60: 612702		



HEIGHTENED TERMINAL		200588
COLOR		MATERIAL
Metallic		Brass
To use with:		
M10 terminals		



INSULATION CAP		
P/N	COLOR	MATERIAL
201010	Red	PVC
202499	Black	PVC
To use with:		
M10 terminals		



MAXICUT[®]

DCW

D.C. Woodhead and Partners Limited
Carlisle Drive - Pudsey - Leeds - LS28 8QS
UNITED KINGDOM

Tel: +44 (0) 113 257 2275
E-mail: info@dcwoodhead.com

Registered in England No 807649
Registered Office: Adastra Works, Carlisle Drive, Pudsey, LS28 8QS

YOUR MANUAL BATTERY SWITCH SOLUTIONS



viatemis.com

 **VIATEMIS**
TEMIS Solutions Group

125 route de Paris
03410 SAINT-VICTOR - France
Tel : +33(0)4 70 08 26 00
Tel : +33(0)4 70 08 26 20
contact@viatemis.com